Basic Information

. Place of Origin: China Brand Name: Bochi

SKHG3700-A Model Number:

 Minimum Order Quantity: 3 sets

• Price: Further communication based on product

configuration and parameters

 Packaging Details: Steel structure packing rack

. Delivery Time: 15-30 days Payment Terms: D/P,T/T

Supply Ability: 3000 sets/months



Product Specification

Length × Width × Height: 4150×1500×2100(mm)

. Curb Weight: 1260(Kg) 2.8m³ . Box Volume: Rated Load: 1000(Kg) • Endurance Mileage: ≥60(Km) • Battery Capacity: 72V150AH

. Highlight: Pure Electric Drive Electric Garbage Cart,

Reasonable Compact Electric Garbage Cart, **Residential Communities Electric Garbage Cart**

Product Description

New Energy Electric Three-Wheeled Rear Bucket Truck SKHG3700-A

This pure electric sanitation vehicle features an optimized rear-loading compression design for efficient urban garbage collection. The stainless steel lightweight body ensures large capacity and leak-proof transport, while hydraulic automation enables hands-free bin docking, lifting, and dumping of standard 120L/240L trash cans.

Constructed with automotive-grade ST16 cab panels for durability, the truck operates via stepless electric drive with integrated differential transmission, delivering quiet, maintenance-free performance. The energy-efficient hydraulic system prevents secondary pollution during waste handling, making it ideal for streets, communities, and public spaces.



product name	Electric three-wheeled rear bucket truck
Length × width × height	4150×1500×2100(mm)
curb weight	1260(Kg)
Box volume	2.8m³
rated load	1000(Kg)
endurance mileage	≥60(Km)
maximum speed	30(Km/h)
wheel base	2810(mm)
Maximum Angle of climb	15°
Rated occupant	1 person
electrical machinery	High torque brushless motor 72V4000W
electronic control	Intelligent controller 72V350A
battery	Lead-acid maintenance battery 12V120AH
charger	Smart charger 72V15A
charging time	Charge 6-8 hours
Lights and signals	LED running light, near and far light, turn signal, LCD instrument, electric horn, reversing voice, work warning light.
hoisting appliance	Pump valve connected, linkage work; 1000W power
hang	Front suspension: steel hydraulic rod, coil spring shock absorber; Rear suspension: main pay steel plate; Non-independent suspension
rear axle	Integrated gearbox drive
tyre	Front: 450-12 Rear: 500-12
braking	Foot mechanical connecting rod drum brake; Manual mechanical parking; Rear wheel action
cab	Die stamping molding, ST16 material. Double sheet metal welding, integral back.









15 Youyi Middle Road, Xishan District, Wuxi City, Jiangsu Province, China